

BioMini Plus 2

PIV Certified Authentication Scanner



| BioMini Plus 2 | Suprema BioMini Plus 2 has been designed to provide high level security solution with its proven reliability of FBI-PIV certification. BioMini Plus 2 features industry's most advanced MDR(multi dynamic range) technology to capture exceptional image quality even under extreme lighting conditions(operates under direct sunlight up to 100,000 LUX).

The scanner also features cutting-edge live fingerprint detection(LFD) technology for improved security against spoofing, and the latest version of multi award-winning Suprema algorithm for better performance. Combined with ergonomic design, high speed USB 2.0 interface and comprehensive SDK solution, BioMini Plus 2 offers superb biometric authentication solution for both public and commercial applications.



BioMini Plus 2

PIV Certified Authentication Scanner



FEATURES



- FBI PIV and FBI Mobile ID FAP10 certificates
- Image compression standard: WSQ



- Multi Dynamic Range (MDR) Technology
- Operates under direct sunlight up to 100,000 LUX



- Live Fingerprint Detection (LFD) Technology
- Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



- New Improved Optical Sensor
- 500dpi optical fingerprint sensor
- Scratch proof IP65 sensor surface



- Easy Integration
- BioMini SDK for easy application development
- Android, MS Windows & Linux compatible
- Multi-threaded code design for multi-core CPU utilization

SPECIFICATIONS

	Image Quality Standards	FBI PIV / FBI Mobile ID FAP10
Sensor	Live Finger Detection	O
	Sensor Type	Optical
	Resolution	500 ppi
	Gray Scale	256 level
	Platen Size (W x L mm)	16.0 x 19.0
	Sensing Area (W x H mm)	16.0 x 18.0
	Image Size (W x H pixels)	315 x 354
H/W	Interface	USB 2.0 High Speed
	Operating Temperature(°C)	-10~50°C
	Operating humidity	10 ~ 90% RH
	Ingress Protection	IP65 (Sensor Surface)
	Dimensions (W x L x H mm)	66 x 90 x 58
	Weight (Kg)	0.17
S/W	Windows	Windows XP, Vista, 7, 8, 8.1, 10 32/64bit
	Linux	Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64bit
	Android Android 4.1(Jelly Bean)and Above	O
	Image Format	RAW, BMP, WSQ, ISO 19794-4
	Template Type	Suprema, ISO19794-2, ANSI-378
Certification	CE	O
	FCC	O
	KC	O
	UL / CB	O
	IEC62471	O
	WEEE	O
	WHQL	O