

# Suprema Thermal Camera

FaceStation 2 with Temperature Detection



Suprema FaceStation 2 with Temperature Detection combines Suprema's face recognition terminal\* with Suprema Thermal Camera to detect users with elevated skin temperature.

- · Suprema Thermal Camera measures skin temperature of a subject's face using advanced thermography technology.
- FaceStation 2 displays the temperature on a GUI raising alerts when a higher than threshold temperature is detected.
- $\cdot \, \text{Suprema Thermal Camera connects via USB interface making deployment quick and easy on new and retrofit installs.} \\$

# Suprema Thermal Camera

FaceStation 2 with Temperature Detection

#### Features -



# Enhanced security and safety

- $\boldsymbol{\cdot}$  Combination of face recognition and skin temperature measurement
- · Audio and visual alerts with optional alarm
- · Bypass mode for skin temperature measure only
- $\cdot$  Temperature data can be optionally saved as event logs



### Accurate temperature measurement

- Fast and accurate measurement using thermographic camera with 19,200 pixels per frame
- · Does not require reference blackbody to measure temperature



# Easy deployment

- · Easy connection with FaceStation 2 via USB
- Comes with a bracket for convenient deployment on new and retrofit installs




### Ergonomic design for convenience

- $\cdot$  Supports extended height range of 145cm 210cm for face recognition and distance of 0.5m 1.3m for temperature measurement
- · Intuitive GUI for notifications
- $\cdot$  Temperature can be displayed both in Celsius and Fahrenheit


# Specifications -

Part Code	TCM10-FS2
Max. Resolution	120 × 160
NETD (Noise Equivalent Temperature Difference)	≤ 50 mK (@25 °C,F# = 1.0)
Field of View	37.2° × 50°(H × V)
Temperature Range	30 °C to 45 °C (86 °F to 113 °F)
Temperature Accuracy	≤± 0.5 °C (0.9°F)
Temperature Distance	Adjustable, 40cm - 80cm (15.7" to 31.5")
Interface	USB
Operating Temperature	0 °C to 50 °C (32 °F to 122 °F)
Dimensions (WxHxD, mm)	70 mm × 46 mm × 22.2 mm (2.76" × 1.81" × 0.87")
Components	Thermal camera with bracket and USB cable, 6 screws (does not include FaceStation 2)
Firmware	v1.3.2 or v1.4.0 and above
Compatible BioStar 2	v2.8.2.90 or v2.8.5 and above

# System Configurations



## Operation Example





Cenmetrix (Pvt) Ltd No. 38, Fife Road, Colombo 05, Sri Lanka.

Phone: +94-11-2508805 | +94-11-5011946 Fax: +94-11-2594551 info@cenmetrix.lk | www.cenmetrix.lk